

接触器型号		CDC6i-06	CDC6i-09	CDC6i-12	CDC6i-18	CDC6i-25	CDC6i-32	CDC6i-38	CDC6i-40	CDC6i-50	CDC6i-65	CDC6i-80	CDC6i-95	
主电路特性														
极数		3级												
额定绝缘电压(Ui)	V	690												
额定工作电压(Ue)	V	380/400, 660/690												
约定发热电流(Ith), AC-1额定工作电流		16	25	25	32	40	50	50	60	80	80	125	125	
额定工作 电流(Ie)	AC-3,380/400V	A	6	9	12	18	25	32	38	40	50	65	80	95
	AC-3,660/690V	A	3.8	6.6	8.9	12	18	22	22	34	39	42	49	49
	AC-4,380/400V	A	2.6	3.5	5	7.7	8.5	12	14	18.5	24	28	37	44
	AC-4,660/690V	A	1	1.5	2	3.8	4.4	7.5	8.9	9	12	14	17.3	21.3
额定工作 功率(Pe)	AC-3,380/400V	kw	2.2	4	5.5	7.5	11	15	18.5	18.5	22	30	37	45
	AC-3,660/690V	kw	3	5.5	7.5	10	15	18.5	18.5	30	33	37	45	45
	AC-4,380/400V	kw	1.1	1.5	2.2	3.3	4	5.4	5.5	7.5	11	15	18.5	22
	AC-4,660/690V	kw	0.75	1.1	1.5	3	3.7	5.5	6	7.5	10	11	15	18.5
机械寿命	万次	1200				1000			900			650		
电气寿命	AC-3	万次	115				95			70				
	AC-4	万次	23				23			12				
操作频率	AC-3	次/时	1200				600							
	AC-4	次/时	300				300							
主回路端子接线能力														
软线	1根导线	mm ²	1...4		1...4	1.5...6	1.5...6	1.5...6	2.5...25			4...50		
不带接线端子	2根导线	mm ²	1...4		1...4	1.5...6	1.5...6	1.5...6	2.5...16			4...25		
软线	1根导线	mm ²	1...4		1...4	1...6	1...6	1...6	2.5...25			4...50		
带接线端子	2根导线	mm ²	1...2.5		1...2.5	1...4	1...4	1...4	2.5...10			4...16		
硬线	1根导线	mm ²	1...4		1...4	1.5...6	1.5...10	1.5...10	2.5...25			4...50		
不带接线端子	2根导线	mm ²	1...4		1...4	1.5...6	1.5...6	1.5...6	2.5...10			4...25		
紧固扭矩	N·m		1.2		1.2	1.8	1.8	1.8	5			9		
线圈														
额定控制电 路电压(Us)	50Hz	V	24、36、48、110、127、220/230、240、380/400、415、440											
	50/60Hz	V	24、36、48、110、127、220/230、240、380/400、415、440											
允许控制回 路电压(Us)	运行	V	安装倾斜角为±22.5° : 85%~110%Us; 安装倾斜角为±5° : 70%~120%Us											
	释放	V	安装倾斜角为±22.5° : 20%~75%Us; 安装倾斜角为±5° : 20%~65%Us											
线圈功耗	吸合	VA	50	60			70			200			200	
	保持	VA	6~9	6~9.5			6~9.5			15~20			15~20	
	功耗	W	1~3	1~3			1~3			6~10			6~10	
辅助触头														
触头规格		10,01	10,01,11					11						
约定发热电流(Ith)	A	10												
额定工作电压 (Ue)	交流	V	380											
	直流	V	220											
额定控制容量	AC-15	VA	360											
	DC-13	W	33											
认证		CCC、CE、SEMKO												

产品型号	电流规格	机械连锁	辅助触头	线圈电压	附件
CDC6i	09	N	10	M	FN
	09: 9A ... 95: 95A	N: 机械连锁	10: 1NO+0NC 01: 0NO+1NC 11: 1NO+1NC	B: 24V ... M: 220V/230V ... Q: 380V/400V ...	FN: 带可逆排 缺省: 无附件