

技术参数 Technical data









材料 Materials	PU
硬度 Hardness	902A
密度 Density	1.24 ± 0.02g/mm
抗拉强度 Resistance to tension	550kg/cm ²
伸长率 Extension ration	450%
撕裂强度 Tear intensity	10kg/mm
磨擦损耗 Wear and tear	35mm ²
适用温度 Suitable temperature	-50~100
耐酸碱度 Acid&alkaline-reisting degree	± 14PH
可耐气压 With stand atmospheric pressure	0.8Mpa(8.2kgf/cm ²)

2)3 气管内外径代码 Tube outerdia & Innedia

代码 / Code	0425	0640	0850	0860	1065	1280	1410	1612
外径 / OD(mm)	φ4.0	φ6.0	φ8.0	φ8.0	φ10.0	φ12.0	φ14.0	φ16.0
内径 / ID(mm)	φ2.5	φ4.0	φ5.0	φ6.0	φ6.5	φ8.0	φ10.0	φ12.0

EN	尼龙管 Nylon
EU	PU管polyurethane

4) 气管颜色 Color

C	B	BU	R	Y	G	W	O
							
透明 Transparent	黑 Black	蓝 Blue	红 Red	黄 Yellow	绿 Green	白 White	桔黄 Orange

特点 Features

- 1、具有极好的耐高压、抗震动、耐腐蚀、耐磨损、耐气候、耐曲折性能
- 2、重量轻，使用方便灵活，便于布管作业
- 3、内外径尺寸精度控制高，适合各种接头
- 4、多种可供选择
1. It is best to with stand high pressure, shock, corruption, deterioration, climate and bent
2. It is light weight and use convenient, suitable for distribute tube
3. The control accuracy of inside&outside diameter is very high, suitable for various splices
4. Wide choose range

